

Model #: CP1350AVRLCD

UPC: 649532013500 MSRP: \$189.99





The Intelligent LCD Series CP1350AVRLCD UPS, designed for mid to high-end computer systems, features dynamic line conditioning and an Intelligent LCD diagnostic display.

Real-time system vitals can be viewed from this Crystal-Blue (see below) display. The unit can be conveniently mounted in a workstation cabinet, or directly on a desktop. The CP1350AVRLCD guards against surges/spikes, and offers battery backup in the event of brownouts, or total power loss.

Automatic Voltage Regulation (AVR) ensures that all your electronics are receiving clean power and maintains a safe voltage level. PowerPanel PE ™ Management Software automatically saves and closes open files and then shuts down the computer system in an intelligent and orderly manner.

The Intelligent LCD Series units are equipped with full dataline protection: RJ11/RJ45 (phone, fax, Ethernet, network, DSL) and RG-6 coax (DSS, cable modem, satellite, cable TV). "Surge-Only" outlets are perfect for the addition of peripherals such as monitors, printers, scanners, iPods, or CD/DVD players.

CyberPower stands behind its products by offering an industry-leading 3-year warranty, professional Technical Support, and Connected Equipment Guarantees of up to \$425,000.

- Intelligent LCD Diagnostic Display: The innovative front panel LCD can be used to display detailed information on the status of your UPS and current power conditions. The LCD displays 11 different diagnostics: Input voltage level, Output voltage level, Automatic voltage regulator, Battery capacity, Runtime estimate, Load level, Output frequency, On battery, Overload, Fault Condition, and Silent mode.
- Automatic Voltage Regulation (AVR) AVR technology will stabilize the AC signal and maintain a safe voltage level without switching to battery-mode. This conserves battery life, and delivers a cleaner signal to your connected
- GreenPower UPS™ GreenPower UPS™ technology significantly reduces UPS energy costs by bypassing the AVR transformer when incoming AC power is clean. This not only dramatically reduces utility consumption, but also reduces heat dissipation and system noise.
- Ultra-Quiet UPS The combination of an advanced ventilation design, high-end system components, and GreenPower UPS™ technology give CyberPower UPS systems the lowest sound emissions in its class. This makes our UPS perfect for desktop applications, audio/video installations, and quiet workstation environments.
- EMI/RFI Provides shielding against electromagnetic interference & radio frequency signals. Most commonly, this is used to prevent line noise or "humming" that occurs over telephone lines or stereo electronics.
- Transformer-spaced Outlets Widely spaced outlets allow you to conveniently add large transformer-based plugs without compromising the utility of other outlets.
- USB Connectivity An HID-compliant USB port enables full integration with built-in power management and auto shutdown features of Windows, Linux, and Mac OS X.
- PowerPanel PE™ Smart Management Software In event of a power outage, PowerPanel saves your open files and will hibernate your PC to increase the run-time on the UPS unit. PowerPanel is guickly and easily installed on any Windows-based PC and is designed to utilize minimal system resources. Diagnostic screens give immediate visuals of the UPS's status, and also include system notifications, event/data logging, and scheduled shutdowns.
- LED Indicators LED status lights indicate Power-On and wiring faults.
- 3-year Warranty CyberPower will replace damaged units if within 3 years of purchase date. We stand behind our products and guarantee quality. CyberPower also offers a #1 rated technical support team that will assist you with product, installation, or warranty concerns --- Free of Charge!
- Windows Vista ™ compatible Our Power Management software has been fully tested and is compatible with Windows 200x, Server, XP, and Vista.



Technical Specifications

General

Model # CP1350AVRLCD **UPS Topology** Line-Interactive

Energy Saving Yes - Green-UPS Energy Saving Technology

Input

Voltage 90 - 140V 57 - 63Hz Frequency Plug Type **NEMA 5-15P**

Cord Length 6 ft

Output

VA 1350 Watts 810 **Automatic Voltage Regulation** Yes

On Battery Waveform Simulated Sine Wave

Outlets - Total

4 x NEMA 5-15R Outlets - Battery & Surge Outlets - Surge-Only 4 x NEMA 5-15R

Transfer Time 4 ms

Battery

Runtime at Full-Load 2 Minutes Runtime at Half-Load 11 Minutes **Battery Specification** 2 x 12V/8Ah

Surge Protection and Filtering

Surge Suppression 1500 Joules

Phone / Ethernet RJ11 / RJ45 1 x RJ11/45 Combo (One-in/One-out)

Coax Protection RG6 1 x RG-6

Management & Communications

Multifunction LCD Readout Indicators

USB Port 1 x HID Compliant

Serial Port 1 x DB9

PowerPanel Personal Edition Software

SNMP / HTTP Remote Monitoring Not Available

Physical

Dimensions (WxHxD) 4" x 9.75" x 13.25"

Weight 24.6 lbs.

Warranty

Product Warranty 3-year warranty. Free Tech Support.

Connected Equipment Guarantee Lifetime **CEG Amount** \$425,000

